



28PH
2834

PATENT
ATTORNEY DOCKET NO. 0059/058002 - 199-1309(2)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Victor STEFANOVIC Art Unit: 2834
 John MILLER Examiner: Gonzalez, J.
Serial No. : 09/769,901
Filed : January 26, 2001
Title : INDUCTION GENERATOR CONTROL WITH MINIMAL SENSOR
 REQUIREMENTS

Commissioner of Patents and Trademarks
Washington, D.C. 20231

TRANSMITTAL LETTER

Sir:

In response to the Office Action dated November 20, 2002,
applicants hereby submit the enclosed papers including an
Amendment under 37 C.F.R. 1.111 and a Terminal Disclaimer to
Obviate a Double Patenting Rejection Over a Prior Patent.

The required fees are calculated below:

Total Claims	<u>20</u>	-	<u>20</u>	=	<u>0</u>	\$0.00
Independent	<u>4</u>	-	<u>4</u>	=	<u>0</u>	\$0.00
Terminal Disclaimer Fee						<u>\$110.00</u>
TOTAL FEE DUE:						<u>\$110.00</u>

THE COMMISSIONER IS AUTHORIZED TO CHARGE ANY OTHER FEES
WHICH MAY BE REQUIRED OR CREDIT ANY OVERPAYMENT TO DEPOSIT
ACCOUNT NO. 19-2586, REFERENCING ATTORNEY DOCKET NO. 0059/058002.
A DUPLICATE COPY OF THIS PAPER IS ENCLOSED. THIS IS A GENERAL
AUTHORIZATION EXCLUDING ONLY PAYMENT OF THE ISSUE FEE.

Respectfully submitted,


Randolph A. Smith
Reg. No. 32,548

Date: February 20, 2003

SMITH PATENT OFFICE
1901 Pennsylvania Ave., N.W.
Suite 200
Washington, DC 20006-3433
Telephone: 202/530-5900
Facsimile: 202/530-5902
Stefanovic022003



PATENT

ATTORNEY DOCKET NO. 0059/058002 - 199-1309(2)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : Victor STEFANOVIC Art Unit: 2834
John MILLER Examiner: Gonzalez, J.
Serial No. : 09/769,901
Filed : January 26, 2001
Title : INDUCTION GENERATOR CONTROL WITH MINIMAL SENSOR
REQUIREMENTS

Commissioner of Patents and Trademarks
Washington, D.C. 20231

AMENDMENT UNDER 37 CFR 1.111

Siri

In response to the Office Action dated November 20, 2002,
please amend the application as follows:

IN THE ABSTRACT

Please substitute the paragraph on pages 27-28 which has been amended as follows:

-- A method of controlling an induction generator such as an automotive starter-alternator or a windmill is disclosed. The method comprises using a minimal number of current sensors and controlling at least one of a machine flux, an output voltage and generator torque, based on the stator or rotor flux magnitude and position. This method comprises measuring a plurality of current amounts; transforming them into a two phase reference system;